according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

SECTION 1. IDENTIFICATION

Product name : Amitraz Solid Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Acute toxicity (Oral) : Category 4

Serious eye damage : Category 1

Skin sensitization : Category 1

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 1B

Specific target organ toxicity

- repeated exposure

Category 2 (Liver, Central nervous system)

GHS label elements

Hazard pictograms







Signal Word : Danger

Hazard Statements : If small particles are generated during further processing, han-

dling or by other means, may form combustible dust concentra-

tions in air.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

H373 May cause damage to organs (Liver, Central nervous

system) through prolonged or repeated exposure.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.

P308 + P313 IF exposed or concerned: Get medical attention. P333 + P313 If skin irritation or rash occurs: Get medical attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Additional Labeling

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 10 %

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Amitraz (ISO)	33089-61-1	50
Aluminium silicate	12141-46-7	>= 10 - <= 20
Calcium carbonate	471-34-1	>= 10 - <= 20
Paraformaldehyde	30525-89-4	2.55
Sodium bis(2-	577-11-7	1

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

ethylhexyl)sulfosuccinate

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention.
Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention.

Harmful if swallowed.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes serious eye damage.

Suspected of causing genetic defects.

May cause cancer.

May cause damage to organs through prolonged or repeated

exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Carbon oxides

Silicon oxides Metal oxides

Nitrogen oxides (NOx)

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Sulfur oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : Static electricity may accumulate and ignite suspended dust

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe dust. Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Keep container tightly closed. Keep away from water.

Protect from moisture.

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides

Explosives Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

15 ma/m³

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

5 mg/m³

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

15 Million particles per cubic foot

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

Dust, nuisance dust and par-

ticulates

10 mg/m³

Value type (Form of exposure): PEL (Total dust)

Basis: CAL PEL

5 mg/m³

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
		exposure)	concentration	
Amitraz (ISO)	33089-61-1	TWA	10 μg/m3 (OEB 3)	Internal

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

II		Wipe limit	1250 µg/100 cm ²	Internal
Aluminium silicate	12141-46-7	TWA (Respirable particulate matter)	1 mg/m³ (Aluminum)	ACGIH
Calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m³ (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m³ (Calcium car- bonate)	NIOSH REL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
		exposure)	concentration	
Formaldehyde	50-00-0	TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
		TWA	0.016 ppm	NIOSH REL
		С	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC
		TWA	0.016 ppm (Formaldehyde)	NIOSH REL
		С	0.1 ppm (Formaldehyde)	NIOSH REL

Engineering measures

Processing may form hazardous compounds (see section 10)

Minimize workplace exposure concentrations. Apply measures to prevent dust explosions.

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn.

If splashes are likely to occur, wear:

Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : white

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : May form explosive dust-air mixture during processing,

handling or other means.

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : Not applicable

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Stable under normal conditions.May form explosive dust-air mixture during processing,

handling or other means.

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed upon

contact with water or humid air.

Conditions to avoid : Exposure to moisture.

Heat, flames and sparks. Avoid dust formation.

Incompatible materials : Oxidizing agents

Water

Hazardous decomposition products

Contact with water or humid : Formaldehyde

air

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 955.73 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 41.96 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

Amitraz (ISO):

Acute oral toxicity : LD50 (Rat): > 400 mg/kg

LD50 (Mouse): > 1,085 mg/kg

LD50 (Guinea pig): > 400 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rat): > 1,600 mg/kg

Aluminium silicate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 2.18 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Calcium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral tox-

icity

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Paraformaldehyde:

Acute oral toxicity : LD50 (Rat, male): 592 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.07 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 10,000 mg/kg

Sodium bis(2-ethylhexyl)sulfosuccinate:

Acute oral toxicity : LD50 (Rat): 3,080 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Amitraz (ISO):

Species : Rabbit

Result : No skin irritation

Aluminium silicate:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

Calcium carbonate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Paraformaldehyde:

Species : Rabbit Result : Skin irritation

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Sodium bis(2-ethylhexyl)sulfosuccinate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Amitraz (ISO):

Species : Rabbit

Result : No eye irritation

Aluminium silicate:

Species : Rabbit

Result : No eye irritation
Method : OPPTS 870.2400

Remarks : Based on data from similar materials

Calcium carbonate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Paraformaldehyde:

Species : Rabbit

Result : Irreversible effects on the eye

Sodium bis(2-ethylhexyl)sulfosuccinate:

Species : Rabbit

Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Amitraz (ISO):

Test Type : Maximization Test

Routes of exposure : Dermal Species : Guinea pig

Result : Not a skin sensitizer.

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Aluminium silicate:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact
Species : Mouse
Result : negative

Calcium carbonate:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact

Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Paraformaldehyde:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact
Species : Mouse
Result : positive

Remarks : Based on data from similar materials

Assessment : Probability or evidence of high skin sensitization rate in

humans

Sodium bis(2-ethylhexyl)sulfosuccinate:

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Skin contact Species : Humans Result : negative

Germ cell mutagenicity

Suspected of causing genetic defects.

Components:

Amitraz (ISO):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Aluminium silicate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Calcium carbonate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Paraformaldehyde:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: positive

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Result: positive

Remarks: Based on data from similar materials

Test Type: in vitro micronucleus test

Result: positive

Remarks: Based on data from similar materials

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: positive

Remarks: Based on data from similar materials

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: positive

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapor)

Result: positive

Remarks: Based on data from similar materials

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: Ingestion

Result: positive

Remarks: Based on data from similar materials

Germ cell mutagenicity -

Assessment

Positive result(s) from in vivo mammalian somatic cell muta-

genicity tests.

Sodium bis(2-ethylhexyl)sulfosuccinate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: equivocal

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

May cause cancer.

Components:

Amitraz (ISO):

Species : Rat
Application Route : Oral
Exposure time : 2 Years

NOAEL : > 10.18 mg/kg body weight

Result : negative

Species : Mouse Exposure time : 2 Years

LOAEL : 2.3 mg/kg body weight

Result : positive

Target Organs : Liver, Stomach

Aluminium silicate:

Species : Rat
Application Route : Ingestion

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Exposure time : 104 weeks Result : negative

Remarks : Based on data from similar materials

Paraformaldehyde:

Species : Rat
Application Route : Ingestion
Exposure time : 105 weeks
Result : negative

Species : Rat
Application Route : Inhalation
Exposure time : 28 Months
Result : positive

Remarks : Based on data from similar materials

Carcinogenicity - Assess- : Sufficient evidence of carcinogenicity in animal experiments

ment

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Amitraz (ISO):

Effects on fertility : Test Type: Three-generation reproduction toxicity study

Species: Rat

Application Route: Oral

Fertility: NOAEL: > 4.8 mg/kg body weight

Result: No significant adverse effects were reported

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Oral

Developmental Toxicity: NOAEL: 3 mg/kg body weight Remarks: No significant adverse effects were reported

Test Type: Embryo-fetal development

Species: Rabbit Application Route: Oral

Developmental Toxicity: NOAEL: 5 mg/kg body weight

Result: Effects on fetal development.

Aluminium silicate:

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Calcium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Sodium bis(2-ethylhexyl)sulfosuccinate:

Effects on fertility : Test Type: Three-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT-single exposure

Not classified based on available information.

Components:

Paraformaldehyde:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Liver, Central nervous system) through prolonged or repeated exposure.

Components:

Amitraz (ISO):

Target Organs : Liver, Central nervous system

Assessment : May cause damage to organs through prolonged or repeated

exposure.

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Repeated dose toxicity

Components:

Amitraz (ISO):

Species : Mouse
NOAEL : 3 mg/kg
Application Route : Oral
Exposure time : 90 Days
Target Organs : Liver

Species : Dog
NOAEL : 0.25 mg/kg
Application Route : Oral
Exposure time : 90 Days

Target Organs : Central nervous system, Liver

Aluminium silicate:

Species : Rat

NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 104 Weeks

Remarks : Based on data from similar materials

Calcium carbonate:

Species : Rat

NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Method : OECD Test Guideline 422

Paraformaldehyde:

Species : Rat, male
NOAEL : 15 mg/kg
Application Route : Ingestion
Exposure time : 105 Weeks

Remarks : Based on data from similar materials

Sodium bis(2-ethylhexyl)sulfosuccinate:

Species : Rat

NOAEL : 750 mg/kg Application Route : Ingestion Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 09/30/2023 1732058-00015 Date of first issue: 06/06/2017 9.0

Experience with human exposure

Components:

Amitraz (ISO):

Ingestion Target Organs: Central nervous system

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Amitraz (ISO):

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.45 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.035 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.04

Exposure time: 91 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.00148

mg/l

Exposure time: 32 d

Toxicity to daphnia and other: aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0011 mg/l

Exposure time: 21 d

Aluminium silicate:

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Calcium carbonate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOELR (Pseudokirchneriella subcapitata (green algae)): 50

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 09/30/2023 1732058-00015 Date of first issue: 06/06/2017 9.0

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to microorganisms NOEC: 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

EC50: > 1,000 mg/lExposure time: 3 h

Method: OECD Test Guideline 209

Paraformaldehyde:

Toxicity to fish LC50 : > 1 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia pulex (Water flea)): > 1 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC (Oryzias latipes (Orange-red killifish)): > 1 mg/l

Exposure time: 28 d

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): > 1 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

EC50: > 10 mg/l Toxicity to microorganisms

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Sodium bis(2-ethylhexyl)sulfosuccinate:

LC50 (Danio rerio (zebra fish)): 49 mg/l Toxicity to fish

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 6.6 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic ErC50 (Desmodesmus subspicatus (green algae)): 82.5 mg/l

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version **Revision Date:** SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

plants Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 22 mg/l

Exposure time: 72 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EC10 (Daphnia magna (Water flea)): 9 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

EC50 (Pseudomonas putida): 164 mg/l Toxicity to microorganisms

Exposure time: 16 h

Persistence and degradability

Components:

Paraformaldehyde:

Biodegradability Result: Readily biodegradable.

Remarks: Based on data from similar materials

Sodium bis(2-ethylhexyl)sulfosuccinate:

Biodegradability Result: Readily biodegradable.

> Biodegradation: 91.2 % Exposure time: 28 d

Bioaccumulative potential

Components:

Amitraz (ISO):

Species: Lepomis macrochirus (Bluegill sunfish) Bioaccumulation

Bioconcentration factor (BCF): 1,333

Partition coefficient: n-

octanol/water

: log Pow: 5.5

Paraformaldehyde:

Partition coefficient: n-

octanol/water

log Pow: -1.40 Remarks: Calculation

Sodium bis(2-ethylhexyl)sulfosuccinate:

Partition coefficient: n-: log Pow: 1.998

octanol/water Remarks: Calculation

Mobility in soil

Components:

Amitraz (ISO):

Distribution among environ- : log Koc: 3.3

mental compartments

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(amitraz (ISO))

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Amitraz (ISO))

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen- : 956

ger aircraft)

Environmentally hazardous : yes

956

956

IMDG-Code

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Amitraz (ISO))

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

49 CFR

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Amitraz (ISO))

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171

Marine pollutant : yes(Amitraz (ISO))

Remarks : Above applies only to containers over 119 gallons or 450

liters.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Paraformaldehyde	30525-89-4	1000	39215

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

Acute toxicity (any route of exposure) Respiratory or skin sensitization

Germ cell mutagenicity

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Amitraz (ISO) 33089-61-1 50 %

US State Regulations

Pennsylvania Right To Know

Amitraz (ISO) 33089-61-1
Calcium carbonate 471-34-1
Aluminium silicate 12141-46-7
Cresol-formaldehyde copolymer 1,2-naphthoquinonediazido-80296-78-2

4-sulfonate

Paraformaldehyde 30525-89-4

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

California Prop. 65

WARNING: This product can expose you to chemicals including Formaldehyde, which is/are known to the State of California to cause cancer, and

Amitraz (ISO), which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Paraformaldehyde 30525-89-4

California Permissible Exposure Limits for Chemical Contaminants

Calcium carbonate 471-34-1

The ingredients of this product are reported in the following inventories:

AICS : not determined


DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CAL PEL : California permissible exposure limits for chemical contami-

nants (Title 8, Article 107)

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

ACGIH / STEL : Short-term exposure limit CAL PEL / PEL : Permissible exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA CARC / PEL : Permissible exposure limit (PEL)

OSHA CARC / STEL : Excursion limit

OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/30/2023

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a

according to the OSHA Hazard Communication Standard



Amitraz Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 9.0 09/30/2023 1732058-00015 Date of first issue: 06/06/2017

guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8