according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

SECTION 1. IDENTIFICATION

Product name : Flumethrin (1%) Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 4

Acute toxicity (Dermal) : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 1B

Specific target organ toxicity

- single exposure (Oral)

Category 1

Specific target organ toxicity:

- repeated exposure (Oral)

Category 1

Specific target organ toxicity

- repeated exposure

Category 2 (Auditory system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :







Signal Word : Danger

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Hazard Statements : H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H360D May damage the unborn child.

H370 Causes damage to organs if swallowed.

H372 Causes damage to organs through prolonged or repeated

exposure if swallowed.

H373 May cause damage to organs (Auditory system) through

prolonged or repeated exposure.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.

P302 + P352 + P312 IF ON SKIN: Wash with plenty of soap and water. Call a doctor if you feel unwell.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P307 + P311 IF exposed: Call a doctor.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical attention.

P337 + P313 If eye irritation persists: Get medical attention.

P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 09/30/2023 4019096-00015 Date of first issue: 02/25/2019 4.8

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---------------|------------|-------------------------|
| Paraffin oil | 8012-95-1 | >= 65.8537 - <= 68.8889 |
| Xylene | 1330-20-7 | >= 10.5556 - <= 11.5854 |
| Flumethrin | 69770-45-2 | >= 1.1111 - <= 1.2195 |
| Toluene | 108-88-3 | >= 0.5556 - <= 0.6098 |

SECTION 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control center immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

Harmful if swallowed.

May be fatal if swallowed and enters airways.

delayed

Toxic in contact with skin. Causes skin irritation. Causes serious eye irritation.

May damage the unborn child.

Causes damage to organs if swallowed.

Causes damage to organs through prolonged or repeated

exposure if swallowed.

May cause damage to organs through prolonged or repeated

exposure.

First Aid responders should pay attention to self-protection, Protection of first-aiders

and use the recommended personal protective equipment

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

nedia

High volume water jet

Specific hazards during fire

fighting

Do not use a solid water stream as it may scatter and spread

fire

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Use explosion-proof electrical, ventilating and lighting equip-

ment.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe mist or vapors.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases Explosives

Gases

Very acutely toxic substances and mixtures

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis | |
|--------------|----------------|--|--|-----------|--|
| Paraffin oil | 8012-95-1 | TWA (Inhal- able particu- late matter) | rticu- | | |
| | | TWA (Mist) | 5 mg/m³ | OSHA Z-1 | |
| | | TWA (Mist) | 5 mg/m³ | NIOSH REL | |
| | | ST (Mist) | 10 mg/m ³ | NIOSH REL | |
| Xylene | 1330-20-7 | TWA | 100 ppm 435 mg/m³ | OSHA Z-1 | |
| | | TWA | 20 ppm | ACGIH | |
| Flumethrin | 69770-45-2 | TWA | 45 μg/m3 (OEB 3) | Internal | |
| | Further inform | Further information: Skin | | | |
| | | Wipe limit 450 µg/100 cm ² I | | Internal | |
| Toluene | 108-88-3 | TWA | 20 ppm | ACGIH | |
| | | TWA | 100 ppm 375 mg/m³ | NIOSH REL | |
| | | ST | 150 ppm 560 mg/m³ | NIOSH REL | |
| | | TWA | 200 ppm | OSHA Z-2 | |
| <u> </u> | | CEIL | 300 ppm | OSHA Z-2 | |
| | | Peak | 500 ppm (10 minutes) | OSHA Z-2 | |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sam- pling time | Permissible concentration | Basis |
|------------|-----------|--------------------------|---------------------|--|---------------------------|--------------|
| Xylene | 1330-20-7 | Methylhippu ric acids | Urine | End of shift (As soon as possible after exposure ceases) | 1.5 g/g creatinine | ACGIH BEI |
| Toluene | 108-88-3 | Toluene | In blood | Prior to last shift of work- week | 0.02 mg/l | ACGIH BEI |
| | | Toluene | Urine | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l | ACGIH BEI |
| | | o-Cresol | Urine | End of | 0.3 mg/g | ACGIH |

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

| Version | Revision Date: 09/30/2023 | SDS Number: | Date of last issue: 04/04/2023 | | |
|---------|---------------------------|---------------|---|--|--|
| 4.8 | | 4019096-00015 | Date of first issue: 02/25/2019 | | |
| | | | shift (As soon as possible after exposure ceases) | | |

Engineering measures

Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., dripless quick connections).

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., open-face

containment devices). Minimize open handling.

Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving. Take note that the product is

flammable, which may impact the selection of hand

protection.

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection : Work uniform or laboratory coat.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets,

disposable suits) to avoid exposed skin surfaces.

Use appropriate degowning techniques to remove potentially

contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aqueous solution

Color : light brown, yellow

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : $129 \,^{\circ}\text{F} / 54 \,^{\circ}\text{C}$

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 0.820 - 0.900 g/cm³

Solubility(ies)

Water solubility : No data available

Partition coefficient: n- : Not applicable

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 09/30/2023 4019096-00015 Date of first issue: 02/25/2019 4.8

octanol/water

Autoignition temperature No data available

Decomposition temperature No data available

Viscosity

Viscosity, kinematic No data available

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weight No data available

Particle size Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity Not classified as a reactivity hazard. Chemical stability Stable under normal conditions. Flammable liquid and vapor.

Possibility of hazardous reac-

tions

Vapors may form explosive mixture with air. Can react with strong oxidizing agents.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Harmful if swallowed. Toxic in contact with skin.

Product:

Acute toxicity estimate: 404.59 mg/kg Acute oral toxicity

Method: Calculation method

Acute toxicity estimate: > 200 mg/l Acute inhalation toxicity

> Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

Acute dermal toxicity Acute toxicity estimate: 402.36 mg/kg

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version 4.8

Revision Date: 09/30/2023

SDS Number: 4019096-00015

Date of last issue: 04/04/2023 Date of first issue: 02/25/2019

Method: Calculation method

Components:

Paraffin oil:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg

Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Flumethrin:

Acute oral toxicity : LD50 (Rat): > 20 mg/kg

LD50 (Mouse): > 20 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2,934 mg/l

Acute dermal toxicity : LD50 (Rat): > 5 mg/kg

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Paraffin oil:

Species : Rabbit

Result : No skin irritation

Xylene:

Species : Rabbit

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Result : Skin irritation

Flumethrin:

Result : No skin irritation

Toluene:

Species : Rabbit

Method : Directive 67/548/EEC, Annex V, B.4.

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Paraffin oil:

Species : Rabbit

Result : No eye irritation

Xylene:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Flumethrin:

Result : Mild eye irritation

Toluene:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Xylene:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact
Species : Mouse
Result : negative

Toluene:

Test Type : Maximization Test

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Routes of exposure : Skin contact Species : Guinea pig

Method : Directive 67/548/EEC, Annex V, B.6.

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Skin contact

Result: negative

Flumethrin:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)

Test system: Salmonella typhimurium

Result: equivocal

Test Type: Chromosomal aberration
Test system: Chinese hamster ovary cells

Result: positive

Remarks: Not classified due to inconclusive data.

Test Type: Chromosomal aberration Test system: Human lymphocytes

Result: negative

Test Type: in vitro micronucleus test

Test system: Mouse Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Toluene:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Intraperitoneal injection

Result: negative

Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: inhalation (vapor) Method: OECD Test Guideline 478

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Flumethrin:

Species : Rat
Application Route : Oral
Exposure time : 2 Years

NOAEL : 0.5 mg/kg body weight

Result : negative

Carcinogenicity - Assess-

ment

Weight of evidence does not support classification as a car-

cinogen

Toluene:

Species : Rat

Application Route : inhalation (vapor)
Exposure time : 103 weeks
Result : negative

Species : Mouse
Application Route : Skin contact
Exposure time : 24 Months
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage the unborn child.

Components:

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Flumethrin:

Effects on fetal development : Test Type: Development

Species: Rat

Application Route: Oral

Developmental Toxicity: NOAEL: 0.36 mg/kg body weight Result: Maternal toxicity observed., Reduced offspring weight

gain., Fetal abnormalities.

Test Type: Development

Species: Rat

Application Route: Oral

Developmental Toxicity: NOAEL: 0.5 mg/kg body weight Result: Maternal toxicity observed., Skeletal malformations.,

Reduced fetal weight.

Test Type: Development

Species: Rabbit

Application Route: Oral

Developmental Toxicity: NOAEL: 1.7 mg/kg body weight

Result: No teratogenic potential.

Reproductive toxicity - As-

sessment

May damage the unborn child.

Toluene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 416

Result: negative

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: positive

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

STOT-single exposure

Causes damage to organs if swallowed.

Components:

Xylene:

Assessment : May cause respiratory irritation.

Flumethrin:

Routes of exposure : Oral

Assessment : Causes damage to organs.

Toluene:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if swallowed. May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Components:

Xylene:

Routes of exposure : inhalation (vapor)
Target Organs : Auditory system

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.2 to 1 mg/l/6h/d.

Flumethrin:

Routes of exposure : Oral

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Toluene:

Routes of exposure : Inhalation

Target Organs : Central nervous system

Assessment : May cause damage to organs through prolonged or repeated

exposure.

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Repeated dose toxicity

Components:

Paraffin oil:

Species : Rat, female LOAEL : 161 mg/kg Application Route : Ingestion Exposure time : 90 Days

Xylene:

Species : Rat

LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapor)

Exposure time : 13 Weeks

Remarks : Based on data from similar materials

Species : Rat LOAEL : 150

LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Flumethrin:

Species : Rat
NOAEL : 0.7 mg/kg
Application Route : Oral
Exposure time : 13 Weeks

Target Organs : digestive system, Skin

Symptoms : decrease in appetite, Skin disorders

Species : Dog NOAEL : 0.88 mg/kg Application Route : Oral Exposure time : 13 Weeks

Target Organs : digestive system, Hair, Skin

Symptoms : decrease in appetite, Skin disorders

Toluene:

Species : Rat
LOAEL : 1.875 mg/l
Application Route : inhalation (vapor)

Exposure time : 6 Months

Species : Rat
NOAEL : 625 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Aspiration toxicity

May be fatal if swallowed and enters airways.

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Components:

Paraffin oil:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Toluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Toluene:

Inhalation : Target Organs: Central nervous system

Symptoms: Neurological disorders

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Paraffin oil:

Toxicity to fish : LL50 (Scophthalmus maximus (turbot)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Acartia tonsa (Calanoid copepod)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Skeletonema costatum (marine diatom)): > 100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

NOELR (Skeletonema costatum (marine diatom)): > 1 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): 10 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l

Exposure time: 35 d

Method: OECD Test Guideline 210

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Flumethrin:

Toxicity to fish (Chronic tox-

icity)

NOEC (Danio rerio (zebra fish)): 0.046 mg/l

Exposure time: 144 h

Toluene:

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

NOEC (Skeletonema costatum (marine diatom)): 10 mg/l Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus kisutch (coho salmon)): 1.39 mg/l

Exposure time: 40 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Ceriodaphnia dubia (water flea)): 0.74 mg/l

Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 84 mg/l

Exposure time: 24 h

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Persistence and degradability

Components:

Xylene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 70 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Toluene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 80 % Exposure time: 20 d

Bioaccumulative potential

Components:

Paraffin oil:

Partition coefficient: n- : log Pow: > 4

octanol/water Remarks: Calculation

Xylene:

Partition coefficient: n- : log Pow: 3.16

octanol/water Remarks: Calculation

Flumethrin:

Partition coefficient: n-

octanol/water

log Pow: 6.2

Toluene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)

Bioconcentration factor (BCF): 90

Partition coefficient: n-

octanol/water

: log Pow: 2.73

Mobility in soil
No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or

death.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1992

Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.

(Xylene, Flumethrin)

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1992

Proper shipping name : Flammable liquid, toxic, n.o.s.

(Xylene, Flumethrin)

Class : 3
Subsidiary risk : 6.1
Packing group : III

Labels : Flammable Liquids, Toxic

Packing instruction (cargo : 366

aircraft)

Packing instruction (passen: 355

ger aircraft)

IMDG-Code

UN number : UN 1992

Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.

(Xylene, Flumethrin)

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1992

Proper shipping name : Flammable liquids, toxic, n.o.s.

(Xylene, Flumethrin)

Class : 3

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Subsidiary risk : 6.1 Packing group : III

Labels : FLAMMABLE LIQUID, TOXIC

ERG Code : 131 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ Calculated produc | |
|------------|-----------|--------------------------------|--------|
| | | (lbs) | (lbs) |
| Xylene | 1330-20-7 | 100 | 863 |
| Toluene | 108-88-3 | 1000 | 163988 |

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Xylene 1330-20-7 >= 10.5556 - <= 11.5854 %

US State Regulations

Pennsylvania Right To Know

Paraffin oil 8012-95-1
Glycerides, mixed decanoyl and octanoyl 73398-61-5
Xylene 1330-20-7
Toluene 108-88-3

California Prop. 65

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Paraffin oil 8012-95-1

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

Xylene 1330-20-7

California Permissible Exposure Limits for Chemical Contaminants

Paraffin oil 8012-95-1 Xylene 1330-20-7

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:

Flammability Health 2 0 Instability

Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-2 / TWA : 8-hour time weighted average OSHA Z-2 / CEIL : Acceptable ceiling concentration

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

OSHA Z-2 / Peak : Acceptable maximum peak above the acceptable ceiling con-

centration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/30/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

according to the OSHA Hazard Communication Standard



Flumethrin (1%) Formulation

Version Revision Date: SDS Number: Date of last issue: 04/04/2023 4.8 09/30/2023 4019096-00015 Date of first issue: 02/25/2019

US / Z8